

FIBERGLASS HOT SWITCH STICKS

DOUBLE ENDED

Fiberglass Handles are manufactured in accordance with the following specifications: ASTM F711, OSHA 1910.269(j), and OSHA 1926.951(d). All handles are made from pultruded, smooth, foam-filled fiberglass. Safety yellow is the primary fiberglass color. It is recommended that handles be wiped clean with a silicote cloth before and after every use.

The most commonly used combinations are shown below. Other lengths are available. Bags are not included but are available.

The **8900** rain guard is a yellow molded EPDM shield held in place with a hose clamp. Rain guards fit over 1-1/4" to 1-1/2" (3.2 cm to 3.8 cm) diameter handles and provide a dry handle area if the sticks are used in the rain.

Cat. No.	Diameter x Overall Length	Weight lbs. (kgs)
CAP & THREADED FERRULE		
10078CH	1" x 6'6" (2.5 cm x 1.98 m)	2 (0.91)
10096CH	1" x 8' (2.5 cm x 2.44 m)	2 (0.91)
12578CH	1 1/4" x 6'6" (3.2 cm x 1.98 m)	2 (0.91)
12596CH	1 1/4" x 8' (3.2 cm x 2.44 m)	3 (1.36)
15078CH	1 1/2" x 6'6" (3.8 cm x 1.98 m)	5 (2.27)
15096CH	1 1/2" x 8' (3.8 cm x 2.44 m)	6 (2.72)

Cat. No.	Diameter x Overall Length	Weight lbs. (kgs)
TWO THREADED FERRULES		
10078HH	1" x 6'6" (2.5 cm x 1.98 m)	2 (0.91)
10096HH	1" x 8' (2.5 cm x 2.44 m)	2 (0.91)
12578HH	1 1/4" x 6'6" (3.2 cm x 1.98 m)	3 (1.36)
12596HH	1 1/4" x 8' (3.2 cm x 2.44 m)	4 (1.81)
15078HH	1 1/2" x 6'6" (3.8 cm x 1.98 m)	3 (1.36)
15096HH	1 1/2" x 8' (3.8 cm x 2.44 m)	6 (2.72)
150120HH	1 1/2" x 10' (3.8 cm x 3.05 m)	6 (2.72)

TWO INSULATED HEX FERRULES		
12578HHM	1 1/4" x 6'6" (3.2 cm x 1.98 m)	4 (1.81)
12596HHM	1 1/4" x 8' (3.2 cm x 2.44 m)	4 (1.81)

CAP & UNIVERSAL FERRULE		
10078CU	1" x 6'6" (2.5 cm x 1.98 m)	2 (0.91)
12578CU	1 1/4" x 6'6" (3.2 cm x 1.98 m)	2 (0.91)
15096CU	1 1/2" x 8' (3.8 cm x 2.44 m)	6 (2.72)

RAIN GUARD		
8900	Rain Guard w/ Hose Clamp	0.2 (0.1)

